

Model Selection

Model	Description H x W x D (in)	Airflow cfm (L/s)					Effectiveness @ 0 °C (32 °F)	Performance Highlights
		.1 (25 Pa)	.2 (50 Pa)	.3 (75 Pa)	.4 (100 Pa)	.5 (125 Pa)		
95 MAX*	Recirculating Defrost 24.5 x 18.5 x 16	76 (36)	73 (34)	70 (33)	66 (31)	60 (29)	88%	Compact design for tight installations. Three top ports and 4th port knockout allows top or side mounting.
155 MAX 155 MAX RX	Recirculating Defrost 19 x 33.62 x 14.75	144 (68)	134 (63)	125 (59)	113 (53)	92 (43)	73%	Most popular HRV. Horizontal with door port balance. Same as 155 MAX, reverse design.
155 ECM*	Recirculating Defrost 19 x 33.62 x 14.75	164 (77)	157 (74)	147 (69)	146 (69)	140 (66)	72%	Same design as 155 MAX, with a highly efficient energy-saving ECM motor.
195 ECM*	Damper Defrost 19 x 49 x 14.75	191 (90)	184 (86)	177 (83)	169 (80)	159 (75)	88%	Dual core for maximum heat recovery and includes energy-saving ECM motor.
200 MAX* 200 MAX RX*	Recirculating Defrost 19 x 33.62 x 14.75	207 (97)	200 (94)	184 (87)	171 (80)	152 (71)	74%	Versatile performance in a variety of regions. Same as 200 MAX, reverse design.
195 DCS*	Damper Defrost 19 x 49 x 14.75	216 (101)	195 (92)	181 (85)	158 (74)	144 (68)	92%	Dual core for maximum heat recovery and energy efficiency.
300 DCS*	Damper Defrost 19 x 49 x 14.75	235 (111)	220 (104)	203 (96)	186 (88)	167 (79)	90%	Same design as 195 DCS except for greater airflows. Meets the needs of high-efficiency in larger homes.

ERV options also available. See your Sales Representative or www.lifebreath.com



Setting a new standard
for energy efficient, clean air homes



Visit us at www.lifebreath.com



This product earned the ENERGY STAR by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. This meets ENERGY STAR requirements only when used in Canada.

Control Options



Lifestyle MAX
Digital Control
#99-DXPL01
(included)



or choose...

Lifestyle MAX
Programmable
Control
#99-LS01

- 5-speed operation
- 4 user operational modes
 - continuous ventilation
 - 20 min. ON, 40 min. OFF
 - 20 min. ON, 40 min. recirculation*
 - continuous recirculation*
- **DELUXE** fully featured 5-speed, 4 mode unit.
- Fully **PROGRAMMABLE**, allowing you to customize for your specific lifestyle.
- Built-in interface to furnace
- Automatic control based on outdoor temperature sensing.
- Automatic service reminder

*Not available on all models

Timers

Lifestyle 20/40/60 Minute Timer #99-DET01

- Initiates high speed operation for 20, 40 or 60 minutes

Lifestyle 20 Minute Timer #99-20M01

- Initiates high speed operation for 20 minutes



Model Selection

Model	Description H x W x D (inches)	Airflow cfm (L/s)					Effectiveness @ 0 °C (32 °F)	Performance Highlights
		.1 (25 Pa)	.2 (50 Pa)	.3 (75 Pa)	.4 (100 Pa)	.5 (125 Pa)		
RNC 95*	Recirculating Defrost 24.5 x 18.5 x 16	76 (36)	73 (34)	70 (33)	66 (31)	60 (29)	88%	Top ported, compact unit. Ideally suited to narrow installations.
RNC5-TPD*	Recirculating Defrost 18.75 x 27 x 15	156 (74)	146 (69)	134 (63)	124 (59)	115 (54)	74%	Compact unit with door port balancing, Adjustable high speed (3) settings.
RNC 120D	Recirculating Defrost 22 x 22.13 x 9.13	142 (67)	137 (64)	131 (62)	128 (60)	123 (58)	68%	Only 9 inches tall. Can be mounted horizontally or vertically for maximum installation flexibility.
RNC 155	Recirculating Defrost 19 x 33.62 x 14.75	144 (68)	134 (63)	125 (59)	113 (53)	92 (43)	73%	Horizontal model, with door port balancing. One of our most popular units.
RNC 200*	Recirculating Defrost 19 x 33.62 x 14.75	207 (97)	200 (94)	184 (87)	171 (80)	152 (71)	74%	Horizontal model, with door port balancing. Same design as RNC 155 with greater airflow.
RNC 10	Damper Defrost 19 x 33.62 x 14.75	177 (83)	164 (77)	156 (73)	143 (67)	123 (58)	76%	Horizontal model with 5 ports and damper defrost. Best value for new construction.
RNC 20	Damper Defrost 19 x 33.62 x 14.75	214 (101)	206 (97)	193 (91)	184 (87)	170 (80)	67%	Same design as RNC 10. Ideally suited to larger applications.



Setting a new standard
for energy efficient, clean air homes



Visit us at www.lifebreath.com

Control Options



Lifestyle
Dehumidistat
#99-DH01

- Initiates high speed ventilation when the indoor humidity level is above the set point.



Lifestyle RNC
Ventilation
Control
#99-BC01

- 2 Speed operation
- Standby
- Unit On/Off
- Dehumidistat



Lifestyle RNC Digital Control #99-DX01

- 4 selectable operational modes*
* Not available on all models
- 2 speed operation on each mode
- Adjustable dehumidistat function
- Dehumidistat disable

Timers

Lifestyle 20/40/60 Minute Timer #99-DET01

- Initiates high speed operation for 20, 40 or 60 minutes

Lifestyle 20 Minute Timer #99-20M01

- Initiates high speed operation for 20 minutes

Accessories

- Weatherhoods - 5", 6" or 7"
- Kitchen Grille - 6" x 10"
- Tech Grilles - 4", 5", 6" or 8"



This product earned the ENERGY STAR® by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. This meets ENERGY STAR requirements only when used in Canada.